


**Features**

Center amplifying gate
Metal case with ceramic insulator
Low on-state and switching losses

Typical Applications

AC controllers
DC and AC motor control
Controlled rectifiers

Part No. Y70KPM-KT60cT

$I_{T(AV)}$	1630A
V_{DRM}, V_{RRM}	4500V 4800V
	5000V 5200V

SYMBOL	CHARACTERISTIC	TEST CONDITIONS	T_J (°C)	VALUE			UNIT
				Min	Type	Max	
$I_{T(AV)}$	Mean on-state current	180° half sine wave 50Hz Double side cooled, $T_C=70^\circ\text{C}$	125			1630	A
V_{DRM} V_{RRM}	Repetitive peak off-state voltage Repetitive peak reverse voltage	$t_p=10\text{ms}$	125	4300		5200	V
I_{DRM} I_{RRM}	Repetitive peak current	at V_{DRM} at V_{RRM}	125			200	mA
I_{TSM}	Surge on-state current	10ms half sine wave	125			18	kA
I^2t	I^2t for fusing coordination	$V_R=0.6V_{RRM}$				1620	$\text{A}^2\text{s}\cdot 10^3$
V_{TO}	Threshold voltage		125			1.25	V
r_T	On-state slope resistance					0.39	$\text{m}\Omega$
V_{TM}	Peak on-state voltage	$I_{TM}=3000\text{A}$, $F=40\text{kN}$	25			3.00	V
dv/dt	Critical rate of rise of off-state voltage	$V_{DM}=0.67V_{DRM}$	125			1000	$\text{V}/\mu\text{s}$
di/dt	Critical rate of rise of on-state current	$V_{DM}=67\%V_{DRM}$ to 3000A, Gate pulse $t_r \leq 0.5\mu\text{s}$ $I_{GM}=1.5\text{A}$	125			250	$\text{A}/\mu\text{s}$
Q_{rr}	Recovery charge	$I_{TM}=2000\text{A}$, $t_p=4000\mu\text{s}$, $di/dt=-20\text{A}/\mu\text{s}$, $V_R=100\text{V}$	125		3000		μC
I_{GT}	Gate trigger current	$V_A=12\text{V}$, $I_A=1\text{A}$	25	40		300	mA
V_{GT}	Gate trigger voltage			0.8		3.0	V
I_H	Holding current			20		250	mA
V_{GD}	Non-trigger gate voltage	$V_{DM}=67\%V_{DRM}$	125			0.3	V
$R_{th(j-c)}$	Thermal resistance Junction to case	At 180° sine double side cooled Clamping force 40.0kN				0.012	C/W
$R_{th(c-h)}$	Thermal resistance case to heatsink					0.0035	
F_m	Mounting force			30		40	kN
T_{stg}	Stored temperature			-40		140	°C
W_t	Weight				880		g
Outline	KT60cT						




Fig.1




Fig.2




Fig.3




Fig.4




Fig.5




Fig.6




Fig.7




Fig.8





Fig.9

Outline:



TECHSEM reserves the right to change specifications without notice.